

AMENDMENTS TO THE CLAIMS

1. (Currently Amended) A method comprising:
dynamically establishing ATM adaptation layer 2 (AAL2) channel identifiers (CIDs) on a call-by-call basis using ATM standards-based call control signaling protocols ~~of an AAL2 signaling layer;~~
~~multiplexing voice information from one channel of a customer premise equipment (CPE) into a plurality of AAL2 packets at a network edge device having a common CID of the AAL2 CIDs; and~~
~~executing a call set-up process in the AAL2 signaling layer, comprising mapping the common CID to a virtual path/virtual channel (VP/VC) that forms part of a virtual user network interface (UNI) to an ATM network and mapping the CIDs to a virtual path/virtual channel (VP/VC) that forms part of a virtual user network interface (UNI) to an ATM network.~~
2. Canceled.
3. (Currently Amended) An apparatus comprising an ATM node configured to:
dynamically establish ATM adaptation layer 2 (AAL2) channel identifiers (CIDs) on a call-by-call basis using ATM standards-based call control signaling protocols ~~of an AAL2 signaling layer;~~
~~multiplex voice information from one channel of a customer premise equipment (CPE) into a plurality of AAL2 packets at a network edge device having a common CID of the AAL2 CIDs; and~~
~~execute a call set-up process in the AAL2 signaling layer, comprising mapping the common CID to a virtual path/virtual channel (VP/VC) that forms part of a virtual user network interface (UNI) to an ATM network and map each of the CIDs to a virtual path/virtual channel (VP/VC) within an ATM standard call control protocol.~~
4. Canceled.

5. (Currently Amended) A method, comprising:
~~multiplexing voice information at a network edge device from one channel of a customer premise equipment (CPE) into a plurality of ATM adaptation layer 2 (AAL2) packets having a common channel identifier (CID); and~~
~~executing a call set-up process in an AAL2 signaling layer, comprising mapping the common CID to a virtual path/virtual channel (VP/VC) as part of a standards-based ATM call control protocol of the AAL2 signaling layer, wherein the VP/VC forms part of a virtual user network interface (UNI) to an ATM network~~ mapping ATM adaptation layer 2 (AAL2) channel identifiers (CIDs) to a virtual path/virtual channel (VP/VC)
within a standards-based ATM call control protocol.
6. (Original) The method of claim 5 wherein the standards-based ATM call control protocol is selected from the list comprising UNI 3.1/4.0 and Q.2931.
7. (Currently Amended) The method of claim 5 wherein the mapping is performed at ~~the~~ a network edge device communicatively coupled to ~~the~~ customer premises equipment.
8. (Original) The method of claim 7 wherein the network edge device is communicatively coupled to the customer premises equipment over time division multiplexed communication channels.
9. (Currently Amended) The method of claim 8 further comprising multiplexing the time division multiplexed communication channels to ~~multiple~~ one or more AAL2 VPs/VCs.
10. (Currently Amended) The method of claim 9 further comprising mapping the ~~multiple~~ one or more AAL2 VPs/VCs to the CIDs prior to mapping the CIDs to the VP/VC.
11. (Currently Amended) Computer-readable instructions, which when implemented by a processor, cause the processor to:
~~multiplex voice information at a network edge device from one channel of a customer premise equipment (CPE) into a plurality of ATM adaptation layer 2 (AAL2) packets having a common channel identifier (CID); and~~

~~execute a call set-up process in an AAL2 signaling layer, comprising mapping the common CID to a virtual path/virtual channel (VP/VC) as part of a standards-based ATM call control protocol of the AAL2 signaling layer, wherein the VP/VC forms part of a virtual user network interface (UNI) to an ATM network map~~ ATM adaptation layer 2 (AAL2) channel identifiers (CIDs) to a virtual path/virtual channel (VP/VC) within a standards-based ATM call control protocol.

12. (Previously Presented) The computer-readable instructions of claim 11, wherein the computer-readable instructions are embodied in a computer readable medium.

13. (Currently Amended) The computer-readable instructions of claim 11 further comprising additional instructions, which when implemented by the processor, cause the processor to multiplex ~~at least one~~ or more time division multiplexed communication channels to ~~multiple one or more~~ AAL2 VPs/VCs prior to mapping the AAL2 CIDs to the VP/VC.

14. (Currently Amended) The computer-readable instructions of claim 13 further comprising yet more instructions, which when executed by the processor, cause the processor to map the ~~multiple one or more~~ AAL2 VPs/VCs to the CIDs prior to mapping the CIDs to the VP/VC.